



No. 005

SAFETY ALERT

TBIT PBB Safety Procedures
October 5, 2018

TBIT Boarding Bridge safety checks to be completed pre-departure and post-departure. (1) Potable water cabinet checks. (2) Ground power hoist fully retracted. (3) Jet-bridge maneuvering area clear of obstructions. (4) Cab doors closed and securely locked. (5) Safety chain securely latched.

1. POTABLE WATER CABINET CHECKS:

- A. Potable water hose must be fully retracted and stowed into cabinet.
- B. Open the nozzle ball valve.
- C. Potable water cabinet doors must be securely locked.
- D. Potable water cabinet beacon light must always be OFF prior to bridge operation.



If the amber beacon is on, either the nozzle coupling is not connected to the air Gap coupling or the nozzle ball valve is in the closed position.

Please ensure the nozzle ball valve is in open position.



2. GROUND POWER UNIT CHECKS:

A. Ground Power Cables must be fully retracted prior to bridge operation.



Please ensure GPU cables are fully retracted prior to PBB operation.

3. CAB DOOR CHECKS:

- A. Cab doors must be secured when operating Jet-Bridge. (Exceptions: Deplaning, and Boarding)
- B. Safety chain must always be securely latched. (Exceptions: Deplaning, and Boarding)



In the event of damage or inoperable equipment please contact below:

Vanderlande / Control Room: (310) 215-1218

TBITEC Hotline: (310) 646-9378